

POP-UP replaces the need for ladders and steps to be used indoors in low level access environments. Its detailed design means that it can offer a multitude of special features that ensure the user has a safe yet simple solution to low level access.

Pop-Up has been designed, manufactured and tested in accordance with both the European Standard EN280 and the safety requirements of the European Machinery Directive 98/37/EC.

#### **Features**

- Immediate low level access in 8 seconds
- Fully stable safe working load of 240 kgs
- Platform height 1.63 mtrs, working height 4.00 mtrs
- Fits through standard doorways and into passenger lifts
- Battery powered elevation with inbuilt variable charger 110 and 240 volt
- Over 300 lifts on one charge
- Simple hand set controls
- No formal training required

#### **Specifications**

- Safe working load (SWL) 240 kg - Equivalent to 1 person + 160 kg tools and materials
- Maximum platform height 1.63 metres
- Maximum working height 3.63 metres
- Platform length 1.01 metres
- Platform width 0.52 metres
- Platform guard rail height 1.10 metres
- 12 volt DC Motor 0.7 kW, Battery 80Ah with built-in charger
- Hydraulic system - Maximum pressure 250 bar
- Reservoir capacity 1 litre
- Raise 8 seconds
- Lower 8 seconds
- Approx number of lifts 300 (fully charged with SWL)
- Stowed dimensions length 1135mm x height 1636mm x 700mm
- Weight 215Kg